






IMPORTANT: These prices are calculated at a Rand:Dollar exchange rate 8:1.



Warranty: Video servers, box-type & mini-dome IP Cameras : 24 months (from the date of delivery)
IR cameras and accessories : **13 months** (from the date of delivery)


★ [H264] - Video Server			
	Model Name	Description	RRP
H.264/MJPEG/MPEG4 (*Dual streams simultaneously)			
	EV3151A	Full D1, Audio, DIO, PTZ Control **WiFi (optional)	R 2,250
	EV3150A - New	Full D1, Audio, 2xDI, 1xDO, PTZ Control, PoE, 12Vdc output	R 2,625
















★ [H264] - Box Type IP Camera			
	Model Name	Description	RRP
H.264/MJPEG/MPEG4 (*Dual streams simultaneously)			
	EV6150-CI	Full D1, 600TVL Sony CCD	R 4,125
	EV6150P-CI	Full D1, 600TVL Sony CCD, POE	R 4,375
	EV6150A-CI	Full D1, 600TVL Sony CCD, D/N ICR, Auto-IRIS, Audio, SD, DIO, RS485, POE, **WiFi (optional)	R 4,625
	EV6151A	VGA CMOS, Audio, SD, DIO, RS485, POE, **WiFi (optional)	R 3,250
	EV6153A	VGA P-Scan Sony CCD, D/N IR-Pass, Auto-IRIS, Audio, SD, DIO, RS485, POE, **WiFi (optional)	R 4,250
	EV6156A	Full D1, Sony WDR 540TVL CCD, D/N ICR, Auto-IRIS, Audio, SD, DIO, RS485, POE, **WiFi (optional)	R 6,000

★ [H264] - IR Outdoor IP Camera			
	Model Name	Description	RRP
H.264/MJPEG/MPEG4 (*Dual streams simultaneously)			
	EV6355A-BO	Full D1, 420TVL Sony CCD, 25mm lens, 50M IR, Audio, DIO	R 5,125
	EV6355AP-CO	Full D1, 520TVL Sony CCD, 25mm lens, 50M IR, Audio, DIO, PoE	R 5,625
	EV6356AP-BO	Full D1, 520TVL Sony CCD, 3.8-9.5mm lens, 35M IR, Audio, DIO, POE	R 6,750
	EV6356AP-CO	Full D1, 520TVL Sony CCD, 9-22mm lens, 35M IR, Audio, DIO, POE	R 7,000
	EV6353A-DO24 EV6353A-DO80	Full D1, WDR 540TVL Sony CCD, Vari-focal Lens:3.8-9.5mm, 40M IR, Audio, DIO	R 12,250
	EV6353A-EO24 EV6353A-EO80	Full D1, WDR 540TVL Sony CCD, Vari-focal Lens:9-22mm, 40M IR, Audio, DIO	R 12,500
	EV6353A-FO24 EV6353A-FO80	Full D1, WDR 540TVL Sony CCD, Vari-focal Lens:9-22mm, 80M IR, Audio, DIO	R 12,750

(*** EV6353 series : 24 stands for 24V AC only / 80 stands for 90V-240V AC ***)

★ [H264] - Dome Type IP Camera			
	Model Name	Description	RRP
H.264/MJPEG/MPEG4 (*Dual streams simultaneously)			
	EV6551A-BI	Full D1, 420TVL Sony CCD, 4/6/8 mm lens, 10M IR, Audio, DIO, IP66	R 3,500
	EV6551AP-BI	Full D1, 420TVL Sony CCD, 4/6/8 mm lens, 10M IR, Audio, DIO, POE IP66	R 3,875
	EV6551A-DI - New	Full D1, 520TVL Sony CCD, 3-Axis, ICR, Vari-focal 3.8-9.5mm, 15-20M IR, Audio, DIO, POE, IP66	R 6,375
	EV6551AP-DI - New	Full D1, 520TVL Sony CCD, 3-Axis, ICR, Vari-focal 3.8-9.5mm, 15-20M IR, Audio, DIO, POE, IP66	R 6,625
	EV6552A	VGA CMOS, 3.6/4.3/6 mm, Audio, DIO, RS485	R 3,000
	EV6552AP	VGA CMOS, 3.6/4.3/6 mm, Audio, DIO, RS485, POE	R 3,250
	EV6552R - New	VGA Low light CMOS, 4mm f1.5 , Audio, DIO, RS485	R 3,250
	EV6552RP - New	VGA Low light CMOS, 4mm f1.5 , Audio, DIO, RS485, POE	R 3,500

★ [H264] - Bullet Type IP Camera			
	Model Name	Description	RRP
H.264/MJPEG/MPEG4 (*Dual streams simultaneously)			
	EV6750 - New	VGA Low light CMOS, 4mm f1.5, IP66	R 3,250

★ [MegaPixel /Full HD/5MP] - Box Type IP Camera "ONVIF"			
	Model Name	Description	RRP
H.264/MJPEG/MPEG4 (*Multi streams simultaneously)			
	EV8150A	[Box type] 1.3MP CMOS (*Entry-level chipset), Audio, D/N ICR, SD, DIO, RS485, POE, **WiFi (optional)	R 3,300
	EV8180A - New	[Box type] 1.3MP CMOS, Audio, D/N ICR, SD, DIO, RS485, POE, **WiFi (optional)	R 4,290
	EV8580A-B - New	[Dome Type] 1.3MP real time, 4mm f1.5 lens, 15M IR, multi-streaming, ROI, Audio, D/N ICR, SD, DIO, RS485, POE, Vandal proof, IP66	R 5,940
	EV8580A-C - New	[Dome Type] 1.3MP real time, fujinon 2.8-10mm vari-focal lens, 15M IR, multi-streaming, ROI, Audio, D/N ICR, SD, DIO, RS485, POE, Vandal proof, IP66	R 6,930
	EV8780A - New (*Coming soon)	[Bullet Type] 1.3MP CMOS, 4.3mm f2.0 lens, 15M IR, IP66	R 4,510
	EV8781A - New (*Coming soon)	[Bullet Type] 1.3MP real time, fujinon 2.8-10mm vari-focal lens, 25M IR, Daul-streaming, ROI, Audio, D/N ICR, SD, DIO, RS485, POE, Vandal proof, IP67, cable management bracket, heater	R 8,580
	EV8180U	[Box type] 2.1MP, 1080P real time, multi-streaming, 4 ROI, Audio, D/N ICR, SD, DIO, RS485, POE, **WiFi (optional)	R 5,610
	EV8580U-B	[Dome Type] 2.1MP, 1080P real time, 4mm f1.5 lens, 15M IR, multi-streaming, ROI, Audio, D/N ICR, SD, DIO, RS485, POE, Vandal proof, IP66	R 7,480
	EV8580U-C	[Dome Type] 2.1MP, 1080P real time, fujinon 2.8-10mm vari-focal lens, 15M IR, multi-streaming, ROI, Audio, D/N ICR, SD, DIO, RS485, POE, Vandal proof, IP66	R 8,800
	EV8780U	[Bullet Type] 2.1MP, 1080P CMOS, 4.3mm f2.0 lens, 15M IR, IP66	R 6,160
	EV8781U - New (*Coming soon)	[Bullet Type] 2.1MP, 1080P real time, fujinon 2.8-10mm vari-focal lens, 25M IR, multi-streaming, ROI, Audio, D/N ICR, SD, DIO, RS485, POE, Vandal proof, IP67, cable management bracket, heater	R 9,900
	EV8782U - New (*Coming soon)	[Bullet Type] 2.1MP, 1080P real time, fujinon motorized lens 2.8-10mm, 25M IR, multi-streaming, ROI, Audio, D/N ICR, SD, DIO, RS485, POE, Vandal proof, IP67, cable management bracket, heater	R 11,440
	EV8180F - New	[Box type] 5MP, 1080P 2.1MP real time, multi-streaming, 8 ROI, Audio, D/N ICR, SD, DIO, RS485, POE, **WiFi (optional)	R 8,580
	EV8580F - New	[Dome Type] 5MP, 1080P real time, multi-streaming, 3.3mm lens, 8 ROI, Audio, D/N ICR, SD, DIO, RS485, POE, Vandal proof, IP66	R 10,120
	EV8383F-B - New (*Coming soon)	[IR outdoor] 5MP, 1080P real time, multi-streaming, 4-12mm or 12-40mm lens, 8 ROI, Audio, D/N ICR, SD, DIO, RS485, Vandal proof, IP66, 40M IR	R 16,940

▲ Note: Etrivision HD megapixel cameras are ONVIF protocol

★ Accessories			
Type	Model Name	Description	RRP
PoE Injector	AC-PI1202	PoE injector with Power Code 802.3af standard compliant, 12W (EU)	R 800
WLAN Antenna	AC-ANT0009	9dBi gain for wireless models	R 125
WLAN Dongle	AC-WL2203-V2	802.11b/g WiFi USB Dongle (built-in antenna inside -fixed) (For **WiFi models : EV3151A, EV615xA, EV8150 series)	R 375
	AC-WL2203-V3	802.11b/g WiFi USB Dongle (with an external antenna - antenna "changeable") (For **WiFi models : EV3151A, EV615xA, EV8150 series)	R 375
Outdoor Enclosure	AC-OEL11550B1	11pcs LED, IR range 120M, 5-50mm vari-focal lens included	R 7,375
	AC-OEX11000B1	11pcs LED, IR range 120M, no lens	R 4,875
IR Illuminator	AC-IRL123012	30M IR illuminator, IP66, Operating temperature: -20°C-50°C	R 1,500
	AC-IRL126012	60M IR illuminator, IP66, Operating temperature: -20°C-50°C	R 2,125
WLAN System	AC-WS000	P-to-P Wireless system IP68 Approval, -30 ~ +70, Range: 1-3Km	R 4,250
	AC-WS100	P-to-P Wireless system IP68 Approval, -30 ~ +70, Range: 3-5Km	R 8,750
	AC-WS200	P-to-P Wireless system IP68 Approval, -30 ~ +70, Range: 5-20Km	R 17,250

▲ Note : ****WiFi (optional)** : needs an additional WiFi USB dongle (AC-WL2203-V2 or AC-WL2203-V3) (Pls see "Accessories")