



H.264 Real time @ Full HD (1920 x 1080) 2 Megapixel IP cameras

	Code	Description	Price (retail ex VAT)	
	AM2290D	Vandal P/T IP Dome (PoE) (IP66)	H.264/MPEG4/MJPEG Tri-CODEC, Pan 355°, Tilt -30~90°, Auto pan and camera tour, built in ICR for D&N, mSD card slot, IP66 vandal and weather proof housing	R 5,568
	AM2560D	Outdoor VF IR IP Cam (PoE) (IP66)	H.264/MPEG4/MJPEG Tri-CODEC, IR LED and ICR for D&N, Vari-focal lens(3-9mm), Photo sensor IR control, IP66 weather proof housing (-40~+50°)	coming soon
	AM2590D	IR IP cam (PoE) (IP66)	H.264/MPEG4/MJPEG Tri-CODEC, IR LED and ICR for D&N, Fixed lens, Photo sensor IR control, IP66 weather proof housing (-40~+50°)	R 4,080
	AM2530D	IR IP cam (PoE) (IP65 with heater & fan)	H.264/MPEG4/MJPEG Tri-CODEC, IR LED and ICR for D&N, 2-way audio, IP65 housing with heater & fan (-40~+50°)	R 5,568
	AM2030D	Vandal IR IP Dome (PoE) (IP66)	H.264/MPEG4/MJPEG Tri-CODEC, IR LED and ICR for D&N, Vari-focal and AI lens, mSD card slot, IP66 vandal and weather proof housing	R 5,640
	AM2630D	Box IP Cam (PoE) (Indoor)	H.264/MPEG4/MJPEG Tri-CODEC, support C/CS mount lens, built in ICR for D&N, mSD card slot, RS485 for P/T scanner	R 3,648
Peripheral				
	AM8211	Wall Mount	Aluminum wall mount for Outdoor IR IP Cam	R 144
	AM8513	Outdoor Housing with IR, H&F	50M IR distance, 12V DC & 24V AC dual, Dimension: 406mm(L) x 145mm (W) x 109mm (H). Weight: Body 3460g + Wall mount: 630g. Heater: 10°C (on) / 28°C (off). Fan: 40°C (on) / 25°C (off). Aluminium material	R 3,552
	AM8252	Wall Mount Bracket	Vandal PT dome, wall mount use	R 456
	AM8316	Megapixel lens	1/3" f=2.8-12mm Vari-focal, F=1.4 DC Iris lens	R 840

Prices are ZAR retail ex VAT. Prices are subject to change without notice

Warranty: 24 months upon invoice date

RAICOM

Tel: +27 21 706 6190

Fax: 086 555 222 8

Email: info@raicom.co.za

▲ The above cameras are compatible with Alnet Systems in accordance with ONVIF